

Product specification

S-Monovette® Serum Gel CAT, 7.5 ml, cap brown, (LxØ):

92 x 15 mm, with paper label



Product information

Product number	01.1602.001
----------------	-------------

Product descriptions

Name	S-Monovette® Serum Gel CAT, 7.5 ml, cap brown, (LxØ): 92 x 15 mm, with paper label
Product number	01.1602.001
Product description	S-Monovette® Serum Gel CAT, preparation: clotting activator/gel, 7.5 ml, membrane screw cap, cap brown, colour code EU/ISO, (LxØ) without cap: 92 x 15 mm, with paper label, label/print: brown, 50 piece(s)/case, sterile

Material & colours

Color of product	transparent
Piston rod material	Polystyrene (PS)
Tube material	Polypropylene (PP)
Piston material	High Density Polyethylene (HD-PE)
Membrane material	Rubber
Closure material	High Density Polyethylene (HD-PE)
Color of cap	brown

Size

Diameter	15 mm
Length excluding cap	92 mm
Length including cap	108 mm
Length including cap and plunger	129 mm
Sample volume	7.5 ml

Product characteristics

Label/Print	With paper label
Color of print/label	brown
Graduation	Fill mark
Сар	Membrane screw cap
Closure type	Screw cap
Connection	Membrane screw cap
Type of collection	venous
Centrifugation recommended	2500 x g
Centrifugation temperature	20 °C
Centrifugation time	10 Min
Liquid-tight	yes

Purity & certification

Satisfies the requirement	IATA, ADR
Product category	In-vitro diagnostic (IVD)
CE certified	CE - manufacturer's self-declaration
Purity standard	sterile
Sterilisation	Electron irradiation
Batched	yes

Packaging

Piece(s) / inner box	50
Piece(s) / case	500
Piece(s) / pallet	24000
Height of inner box	82 mm
Width of inner box	134 mm
Depth of inner box	189 mm
Height of case	146 mm
Width of case	400 mm
Depth of case	435 mm
Volume of case	0.0254 cbm
Weight of case	5.24 kg

Page2

EAN inner box EAN case 4038917131797 4038917023979

This is the current specification for this product. Sarstedt reserves the right to make changes, in full or in part, at any time without prior notification.

This document was prepared by EDP support and is valid without signature.

This specification is confidential and the property of Sarstedt. It is neither to be duplicated nor made available to third parties without our prior written consent.

